FM APPROVED SLCAB/SLMCAB CONNECTION/TERMINATION KITS




Ordinary Locations Hazardous (Classified) Locations Class I, Division 1^\dagger and 2, Groups B, C, D Class II, Division 2, Group F, G Class III, Division 2

Approvals valid only when used with appropriate heating cable and installation accessories, and installed in accordance with all applicable instructions, codes, and regulations.

 † Contact a BriskHeat representative for information on Division I hazardous location systems.











SLCABSK Splice Kit

Ordinary or Class I Division 2 Locations Kits — FM Approved

Part No.	Kit	Compatible with	Enough to Complete	Kit Contents	Required Accessories
SLCABUC	SLCAB Universal Connection Kit - FM Approved	SLCAB Heating Cable	1 input connection and 2 end terminations; or 1 input power splice	(1) 0.75 in (19 mm) NPT pipe standoff (2) Ring terminals (4) Large, insulated crimp connectors (2) Small, insulated crimp connectors (2) Pipe straps — for 2 in to 6 in (51 mm to 152 mm) 0.D. pipes (1) 6 in (152 mm) shrink sleeve (1) Ground screw (1) 3 oz (89 ml) tube of RTV sealant (1) Roll of fiberglass adhesive tape (1) Caution label	0.75 in (19 mm) NPT junction box —with appropriate approvals.
SLCABSK	SLCAB Splice Kit - FM Approved	SLCAB Heating Cable	10 tee splices or 10 input power connections	(20) Large yellow crimp connectors(20) Large blue crimp connectors(10) Heat shrink tubes(1) 3 oz (89 ml) tube of RTV sealant	
SLMCABUC	SLMCAB Universal Connection Kit - FM Approved	SLMCAB Heating Cable	1 input connection and 2 end terminations; or 1 input power splice; or 1 tee splice	(1) 0.75 in (19 mm) NPT pipe standoff (2) Ring terminals (3) Large, insulated crimp connectors (2) Small, insulated crimp connectors (2) Pipe straps — for 2 in to 6 in (51 mm to 152 mm) 0.D. pipes (2) End boots (1) Ground screw (1) 3 oz (89 ml) tube of RTV sealant (1) Roll of fiberglass adhesive tape (1) Caution label	0.75 in (19 mm) NPT junction box —with appropriate approvals.
SLCABKC	SLCAB End Seal Kit - FM Approved	SLCAB Heating Cable	10 end terminations	(10) Heat shrink tubes	
SLMCABKC	SLMCAB End Seal Kit - FM Approved	SLMCAB Heating Cable	10 end terminations or 10 input power connections	(10) End boots (4) Rolls of fiberglass adhesive tape (1) 3 oz (89 ml) tube of RTV sealant	

FM APPROVED SLCAB/SLMCAB CONNECTION/TERMINATION KITS



SLCABUC1 Class I, Division 1 Power Connection Kit



SLCABKC1 Class I, Division 1 End Termination Kit

Class I Division 1 Kits — FM Approved

Part No.	Kit	Compatible with	Enough to Complete	Kit Contents
SLCABUC1	Class I, Division 1 SLCAB and SLMCAB Power Connection Kit - FM Approved	SLCAB-BF1/ SLMCAB-BF1 Heating Cable	1 power connection. C1D1 junction box included	(1) Junction box with cover (1) Seal fitting (1) Standoff "T" fitting (1) 0.75 in (19 mm) NPT threaded plug (2) 16-14 AWG insulated butt connector (1) Closed end crimp connector (1) 3 oz (89 ml) tube of RTV sealant (1) Sealing compound (2) Pipe straps — for 2 in to 6 in (51 mm to 152 mm) 0.D. pipes (1) Roll of fiberglass adhesive tape (1) Caution label
SLCABKC1	Class I, Division 1 SLCAB and SLMCAB End Termination Kit - FM Approved	SLCAB-BF1/ SLMCAB-BF1 Heating Cable	1 end termination. C1D1 junction box included	(1) Junction box with cover (1) Seal fitting (1) Standoff "T" fitting (2) 0.75 in (19 mm) NPT threaded plug (1) 12-10 AWG spade tongue terminal (1) Silicone rubber boot (1) Silicone sealant (1) Sealing compound (2) Pipe straps — for 2 in to 6 in (51 mm to 152 mm) 0.D. pipes (1) Roll of fiberglass adhesive tape (1) Caution label

EASY WAYS TO ORDER

- 1. Contact your local distributor. Check BriskHeat.com to locate a local distributor.
- 2. Call BriskHeat® at 800-848-7673 or 614-294-3376. We have a staff of application specialists to solve your unique needs.
- 3. Order online at BriskHeat.com 24/7.

PAYMENT TERMS

Credit Card Options









Net 30 Option

Net 30 Terms are available to qualified companies. Please contact your Account Manager for additional details.