

IBC /TOTE TANK HEATERS

Wet-area Wrap-around IBC / Tote Tank Heaters and Insulators
(TOTEW | TOTEWI Series)

NEW!

- ▶ Extra-durable, water resistant design for outdoor/ indoor use and in wash-down environments
- ▶ Insulated, full-coverage design
- ▶ Heater has easy-to-program digital controller: Adjustable up to 140 °F (60 °C)
- ▶ Lightweight and easy-to-install with adjustable buckles
- ▶ Suitable for both metal and plastic IBC / Tote Tanks

Benefits:

- Ideal for a wide range of environments including outdoor and wash-down locations
- Even heat distribution and maximum energy efficiency
- Does not contaminate or scorch your product
- Easy-to-use — simple plug-and-play design
- Reusable and rugged — long service life
- Safe — heater has unique 360° grounded heating element and cool-touch surface for your safety



Heater — All-in-one, plug-and-play solution

Image above shown with optional top cover (sold separately)



Insulator — Pairs nicely with BriskHeat® IBC /Tote Tank Immersion Heater.
See [page 5-21](#)

Image above shown with optional top cover (sold separately)

**PLUG
and
PLAY**



**Water
Resistant**



Easy-to-program digital controller



Adjustable Nylon Straps with Buckles

IBC /TOTE TANK HEATERS

Wet-area Wrap-Around IBC/Tote Tank Heaters and Insulators

(TOTEW | TOTEWI Series)

Specifications:

- Outer Material:** Extra-durable polyester cloth
- Insulation:** 0.5 in (13 mm) thick closed-cell neoprene
- Closure Method:** Adjustable straps with buckles
- Maximum Exposure Temperature:** 180°F (82°C)
- Height:** 36 in (914 mm), 42 in (1067 mm), or 48 in (1220 mm)
- Circumference:** Fits any vessel from 160 in (4064 mm) to 192 in (4877 mm)
- Ingress Protection Rating:** IP54

Additional specifications for heater:

- Operating Temperature:** Up to 140°F (60°C)
- Digital Control:** Programmable in °F and °C
- Built-in High-Limit Safety Thermostat:** 185°F (85°C)
- Heating Element:** 360° grounded heating element for your safety
- Dielectric Strength:** Over 2000 Volts
- Power Cord:** 6 ft (1.8 m) long
- 120 VAC: 3-prong grounded plug (NEMA 5-15P)
- 240 VAC: 3-prong grounded plug (NEMA 6-15P)



Heater
(TOTEW series)

Insulator
(TOTEWI series)



Optional Insulating Cover



Certified to UL safety standards
Approval is for heater

Ordering Information:

Heaters:

Part No. 120VAC	Part No. 240VAC	Height in (mm)	Capacity gal (l)	Tank Perimeter Minimum in (mm)	Tank Perimeter Maximum in (mm)	Weight lbs (kg)
TOTEW361-ADJV	TOTEW362-ADJV	36 (914)	175 - 250 (640 - 950)	160 (4060)	192 (4880)	19 (9)
TOTEW421-ADJV	TOTEW422-ADJV	42 (1067)	275 (1000)	160 (4060)	192 (4880)	23 (10)
TOTEW481-ADJV	TOTEW482-ADJV	48 (1220)	330 (1250)	160 (4060)	192 (4880)	26 (12)

Insulators:

Part No.	Height in (mm)	Capacity gal (l)	Tank Perimeter Minimum in (mm)	Tank Perimeter Maximum in (mm)	Weight lbs (kg)
TOTEW36IV	36 (914)	175 - 250 (640 - 950)	160 (4060)	192 (4880)	16 (7)
TOTEW42IV	42 (1067)	275 (1000)	160 (4060)	192 (4880)	20 (9)
TOTEW48IV	48 (1220)	330 (1250)	160 (4060)	192 (4880)	23 (11)

Accessories:

Description	Part No.
Optional insulated top cover	TOTEW-TOPV

Dimensions of top cover: 40 x 40 in (1016 x 1016 mm) with 4 in (102 mm) wide flaps. Flaps expand maximum dimensions to 48 x 48 in (1219 x 1219 mm)
Insulation thickness of top cover: 0.25 in (6 mm)