SIEMENS

Process Instrumentation

Data Sheet

SIPART PS2 Integral Volume Booster

Smart Valve Positioner

Climate class

1K5, but -40 ... +80 °C Storage

(1K5, but -40 ... +176 °F)

2K4, but -40 ... +80 °C Transport

(2K4, but -40 ... +176 °F)

4K3, but -30 ... +80 °C Operation

(4K3, but -22 ... +176 °F)

Weight

Makrolon

Booster, SA With PS2 4.0 kg (8.8 lbs)

Kit only 2.9 kg (6.5 lbs)

Booster, DA With PS2 5.3 kg (11.7 lbs)

Kit only 4.3 kg (9.4 lbs)

Weight

Explosion proof

Booster, SA With PS2 7.9 kg (17.4 lbs)

Kit only 3.3 kg (7.3 lbs)

Booster, DA With PS2 9.3 kg (20.5 lbs)

Kit only 4.7 kg (10.4 lbs)

Connections Pneumatic connections- 1/2" NPT

Female

Gauge Connections: 1/8" NPT

Auxiliary compressed air, carbon dioxide Power

(CO2), nitrogen (N2), and noble (air supply)

Pressure 1.4...7 bar (20.3...101.5 psi)

Air Quality to ISO 8573-1

Air 1.2 x 10⁻² Nm³/h (0.007

Consumption SCFM)

Vibration

Resistance 150 m/s² (492 ft/s²), Bumping 6ms, 1000 shocks/axis (half-sine) Harmonic Oscillations

compliant to ISA-S75.13

1/4"-18 NPT thread with SS case Gauge

gauges, brass movement scaled

in: Mpa, bar, psi IP66 Rating

Flow Capacity Cv 2.0

Material Anodized Aluminum Body, Brass, Stainless

Steel, Nitrile, Polyester, Teflon, Bronze,

Buna-N



Ordering Information

The booster can be ordered as a kit to add to an existing positioner in the field, or can

ordered as an option on a new unit.

Kit Numbers

6DR4004-1RK Single Acting for positioner with Makrolon enclosure, $\frac{1}{2}$ " NPT connections.

6DR4004-2RK Double Acting for positioner with Makrolon enclosure, $\frac{1}{2}$ " NPT connections.

6DR4004-1RQ Single Acting for positioner with flameproof enclosure, ½" NPT connections.

6DR4004-2RQ Double Acting for positioner with flameproof enclosure, $\frac{1}{2}$ " NPT connections.

Model Option Codes

R1K Single Acting for positioner with Makrolon enclosure, $\frac{1}{2}$ NPT connections.

R2K Double Acting for positioner with Makrolon enclosure, $\frac{1}{2}$ NPT connections.

R1Q Single Acting for positioner with flameproof enclosure, $\frac{1}{2}$ " NPT connections.

R2Q Double Acting for positioner with flameproof enclosure, $\frac{1}{2}$ NPT connections.

Siemens Industry, Inc. 3333 Old Milton Parkway Alpharetta, GA 30005 1-800-241-4453

info.us@siemens.com

Order No. A5E35135282A | Printed in USA | © 09.2014, Siemens AG